


14D 15D Dimensions, Capacities, &c. Number Galls, water Water Full per hour No. contents capacity Height bottom base lbs. inches inches plate 50 to 150 inches pings 2-13in. flows and returns  $2-1\frac{1}{2}$ in. flows and returns  $2-1\frac{1}{2}$ in. flows and returns 2-2in. flows and returns 2-2in. 132 flows and returns Open fire No. 1 1-1½in. flows and returns  $19\frac{1}{2}$   $1-1\frac{1}{2}$  in. flows and returns





## Ideal Hot Water Supply

Although the bath has always been acknowledged as an indispensable aid to health and beauty, the average home seldom has facilities for providing in sufficient quantity its necessary complement—Hot Water.

This is due to the very limited capacity of the kitchen range boiler, which also has the additional drawback that only a small portion of its surface is directly exposed to the fire. Consequently it is practically impossible to obtain any appreciable quantity of hot water, while considerable stoking and waste of fuel are always involved. The installation of a separate appliance for the bath water only entails extra expense, and, moreover, does not satisfy the many other household demands.


To remedy these conditions and ensure an unfailing supply of hot water at small cost, has been the object and achievement of the Ideal Domestic Boiler, and its success is amply evidenced by the comfort and convenience now being enjoyed in thousands of homes.

In the Ideal Domestic Boiler the whole of the internal surface is backed by water and in direct contact with the fire and heated gases, ensuring a maximum transmission of heat to the water. The waterways extend to the floor line and are sufficiently wide to provide large water storage capacity in the boiler itself, and enable any deposit to be easily removed through the cleanout openings.

The fire requires attention only twice or three times daily, and if "banked" at night a plentiful supply of hot water is available in the early morning. Broken gas coke can be used, and dry refuse consumed.








The illustration shows an Ideal Domestic Boiler connected to the same piping as the kitchen range boiler, to which it acts as auxiliary when the range is in use. At other times, with a slow burning fire, it provides ample hot water for all household needs.

An Ideal Damper Regulator automatically controls the draught to the fire and maintains the water at any desired degree, keeping the fuel consumption down to a minimum.

A cast iron baseplate can be provided for use on a wood floor.







The inefficient or worn-out kitchen range is very often entirely removed and replaced by an Ideal Domestic Boiler, the cooking then being done by gas. This makes a clean and effective combination.

Your local plumber will quote you for complete installation, but we shall be glad to advise on the most suitable size Boiler, Cylinder, etc., necessary to get the best results and in the most economical manner.









Digitized by:



ASSOCIATION
FOR
PRESERVATION
TECHNOLOGY,
INTERNATIONAL
www.apti.org
Austraslasian Chapter

## BUILDING TECHNOLOGY HERITAGE LIBRARY

https://archive.org/details/buildingtechnologyheritagelibrary

from the collection of:

Miles Lewis. Melbourne

funding provided by:

the Vera Moore Foundation, Australia



## Digitized by:



ASSOCIATION
FOR
PRESERVATION
TECHNOLOGY,
INTERNATIONAL
www.apti.org
Australasian Chapter

BUILDING TECHNOLOGY HERITAGE LIBRARY

https://archive.org/details/buildingtechnologyheritagelibrary

from the collection of:

Miles Lewis, Melbourne

funding provided by:

the Vera Moore Foundation, Australia

